



| DASH NO | (g) A | B | C +.010 -.015 | D | F | G | H | R RAD |
|---------|-------|-------|---------------------|-------|------|------|------|----------|
| -1 | .965 | 1.115 | .150 | 1.078 | .125 | .300 | .165 | .032 |
| -2 | 1.875 | 2.000 | | 1.955 | | .315 | .160 | |
| -3 | 2.045 | 2.140 | .215 | 2.015 | .150 | .430 | .275 | |

(a) DIMENSION A MUST BE HELD WITHOUT DISTORTION AT END.

MATERIAL: CORROSION RESISTANT STEEL WIRE, QQ-W-423, COMPOSITION F5302, CONDITION B.
DIMENSIONS IN INCHES. UNLESS OTHERWISE SPECIFIED, TOLERANCES: DECIMALS ±.015. UNLESS OTHERWISE SPECIFIED, ALL INTERNAL RADIUS .032 +.000, -.015.

FOR LOCK CLIPPING OF AIRCRAFT TURNBUCKLES, SEE MS33736.
ENDS OF LOCKING CLIP SHALL BE CUT SQUARE AND SHALL BE FREE OF BURRS.

Ⓢ LOCKING CLIPS ARE FOR ONE TIME USE ONLY AND SHALL NOT BE REUSED.

Ⓢ REVISED AND REDRAWN FOR DESIGN FEATURE PURPOSES, THIS STANDARD TAKES PRECEDENCE OVER PROCUREMENT DOCUMENTS REFERENCED HEREIN. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATIONS FOR BID.

| | | | |
|---|------------------------|------------------------------------|-------------------------------|
| P. A. AF-82 Other Code: NAVY - AS ARMY - AV AF - 99 | INTERNATIONAL INTEREST | TITLE CLIP, LOCKING, TURNBUCKLE | MILITARY STANDARD MS 21256 |
| PROCUREMENT SPECIFICATION MIL-T-8878 | SUPERSEDES: | SHEET | OF |

USER ACTIVITY: NAVY - MC

REVIEW ACTIVITY: DLA-1S

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

APPROVED 1 NOV 61
REVISED A 1 JUNE 62 B 25 NOV 63 C 1 MARCH 68